

WS Series**Features**

- Accuracy— 0.1% of full scale
- Capacity—
15 kg x 0.005 kg / 30 lb x 0.01 lb
60 kg x 0.02 kg / 150 lb x 0.05 lb
120 kg x 0.1 kg / 400 lb x 0.2 lb
- Construction— Low profile stainless steel platform with mild steel understructure, stainless steel/ABS indicator with wall bracket and desk mount included
- Power— Four AAA batteries or 6 VDC, 500mA adapter (both included)
- Display— Five digit 17 mm / 0.85" digits with seven segment LCD
- Operator Keys— On/Off/Zero, Tare, Unit, Hold/Print

**Specifications**

Unit: kg, lb, lb/oz

RS-232: 10' interface cable (DB-9) (included)

Battery Life: 20 hours

Operating Temperature: 5° C to 35° C / 41° F to 95° F

Platform Dimension (L x W x H):
380 mm x 305 mm x 27 mm / 15" x 12" x 1"Indicator Dimension (L x W x H):
185 mm x 30 mm x 81 mm / 6.5" x 1.2" x 3.2"

Product Weight: 4 kg / 9 lb

Packaging Dimension (L x W x H):
500 mm x 450 mm x 80 mm / 20" x 18" x 3"

Certifications: CE, RoHS 3, WEEE

Part Number	Model	Capacity	Ship Weight
816985002238	WS15	15 kg x 0.005 kg / 30 lb x 0.01 lb	6 kg
WS08000AAZAAAA	WS80	60 kg x 0.02 kg / 150 lb x 0.05 lb	6 kg
WS12000AAZAAAA	WS120	120 kg x 0.1 kg / 400 lb x 0.2 lb	6 kg

