

# Product datasheet

Specifications



## Power Cord, Locking C19 to IEC309-16A, 3.0m



AP8758

### Overview

**Presentation** Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.

**Lead time** Usually in Stock

### Main

<b>Product or component type</b>	Power cord
<b>Input Connection Type</b>	IEC 60309 16 A 2P + E
<b>Cable length</b>	3.00 m

### Physical

<b>Height</b>	43.2 cm
<b>Width</b>	15.2 cm
<b>Depth</b>	10.2 cm
<b>Net weight</b>	0.49 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Not rack-mountable

### Input

<b>Max line current</b>	16 A
<b>Input current limits</b>	16 A

### Output

<b>Max current draw</b>	16 A
<b>Number of power socket outlets</b>	1 IEC 60320 C19
<b>Power cable length</b>	3.05 m

### Conformance

<b>Product certifications</b>	VDE
-------------------------------	-----

### Environmental

<b>Ambient air temperature for operation</b>	0...70 °C
--	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...70 °C
Storage Relative Humidity	20...80 %
Storage altitude	0.0000000000...15240.0000000000 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.2 cm
Package 1 Width	15.2 cm
Package 1 Length	10.2 cm
Package 1 Weight	0.49 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

### Environmental footprint

Carbon footprint (kg CO2 eq,  
Total Life cycle) **154**

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled  
cardboard **No**

Packaging without single use  
plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **1cdb2fed-  
a06f-4574-913d-8df8e70936b2**

REACH Regulation [REACH Declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile [End of Life Information](#)

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

Take-back

Yes

---