Specifications



APC NetShelter Metered Rack PDU, 2U, 1PH, 7.4kW 230V 32A, x12 C13 and x4 C19 outlets, IEC 309 cord

AP7822B

Overview

Lead time

Lead time	Usually in Stock	
Main		
Product or component type	PDU	
PDU type	Metered	
Cord length	3.7 m	
Number of cables	1	
Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets User manual	

Complementary

e e inpressionen g	
Input Voltage	200 V 208 V 230 V
Height	8.8 cm
Width	44.4 cm
Output Voltage	230 V
Depth	11.2 cm
Net weight	3.36 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Rack-mounted
Rack units	2U
Mounting position	Horizontal
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Outlet type and quantity	12 IEC 60320 C13 4 IEC 60320 C19

Product certifications	C-Tick CE GOST IRAM MIC VDE VCCI
Standards	FCC part 15 class A ICES-003
Ambient air temperature for operation	-545 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	0.00000000015240.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14 cm
Package 1 Width	36.8 cm
Package 1 Length	50.8 cm
Package 1 Weight	5.42 kg

Logistical informations

Country of origin	IN
Contractual warra	anty
Warranty	2 years repair or replace

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

How this information helps you >

Ø Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	8952
Environmental Disclosure	Product Environmental Profile

Use Better

S Materials and Substances	
Packaging made with recycled cardboard	Νο
Packaging without single use plastic	Νο
EU RoHS Directive	Compliant with Exemptions
SCIP Number	1cdb2fed- a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Energy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

\circlearrowright Repack and remanufacture	
Circularity Profile	End of Life Information

Life Is On Schneider

Removable battery	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Yes

Product datasheet

Image of product / Alternate images

Alternative





Product datasheet

