

Product datasheet

Specifications



APC Back-UPS Pro, 1600VA/
960W, Tower, 230V, 8x IEC C13
outlets, Sine Wave, AVR, USB
Type A + C ports, LCD, User
Replaceable Battery

BR1600SI

Overview

Lead time Usually in Stock

Main

| | |
|---------------------------|--|
| Main Input Voltage | 230 V |
| Main Output Voltage | 230 V |
| Rated power in W | 960 W |
| Rated power in VA | 1600 VA |
| Product or component type | Uninterruptible power supply (UPS) |
| Input Connection Type | IEC 60320 C13 |
| output connection type | 6 IEC 60320 C13 2 IEC 60320 C13 surge |
| Battery type | Lead-acid battery |

Batteries & Runtime

| | |
|--|---------------------------------------|
| Run Time | View Runtime Graph |
| Efficiency | View Efficiency Graph |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 16 h |
| Number of battery replacement quantity | 1 |
| Battery voltage | 24 V |
| Battery capacity | 9.4 Ah |
| Battery charger power | 16 W rated |
| Battery life | 3...5 year(s) |
| Replacement battery | APCRBC163 |
| Extended runtime | 0 |

General

| | |
|-----------------------------------|--------------------------|
| Provided equipment | user manual USB cable |
| Number of power module free slots | 0 |

| | |
|-------------------------------------|----|
| Number of power module filled slots | 0 |
| Redundant | No |

Physical

| | |
|---------------------|--------------------|
| Colour | Black |
| Height | 26 cm |
| Width | 10 cm |
| Depth | 36.8 cm |
| Net weight | 12.1 kg |
| Mounting preference | No preference |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | No |

Input

| | |
|----------------------------|--------------------------------|
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Input voltage limits | 176...294 V |
| Maximum input current | 10 A |
| Switching current capacity | 10 A |

Output

| | |
|----------------------------------|---------------------------------|
| Maximum configurable power in W | 960 W |
| Output frequency | 50/60 Hz +/- 1 Hz sync to mains |
| UPS type | Line interactive |
| Maximum configurable power in VA | 1600 VA |

Conformance

| | |
|------------------------|--|
| Product certifications | A-Tick C-Tick CE EAC RCM TISI |
| Marking | GS Mark |
| Standards | EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018 |

Environmental

| | |
|---------------------------------------|---------------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0.000000000...15240.000000000 m |

| | |
|------------------|------------|
| Acoustic level | 45 dBA |
| Heat dissipation | 19.5 Btu/h |

Communications & Management

| | |
|---------------|--|
| control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|-------------------|---|
| Surge energy rate | 509 J |
| Noise suppression | Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous |

Packing Units

| | |
|------------------------------|----------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 35.9 cm |
| Package 1 Width | 48.2 cm |
| Package 1 Length | 22.3 cm |
| Package 1 Weight | 13.75 kg |
| SCC14 | 10731304346927 |

Contractual warranty

| | |
|----------|--|
| Warranty | 2 years repair or replace, 3 years repair or replace for European Union countries and UK |
|----------|--|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

EU RoHS Directive **Compliant with Exemptions**

SCIP Number **019b51cf-d7f1-4f06-ac85-1378fc94c7aa**

REACH Regulation [REACH Declaration](#)

China RoHS Regulation [China RoHS declaration](#)

Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

Use Again

Repack and remanufacture

[Circularity Profile](#)

[End of Life Information](#)

Removable battery

User replaceable

Take-back

Yes
