



XM1255™

Offering lamination or adhesive in one easy to use package, the XM1255 makes applying adhesive to mock-ups, storyboards or protection of drawings and documents up to A3 width fast and easy.

Instantly applies laminate, adhesive or both without heat or electricity. Simply feed the item, turn the handle and trim. No smell, no mess, no waiting.

- Aggressive adhesive, coupled with high pressure rollers, improves both transfer and bonding qualities
- Patented drop-in cartridges allow quick and easy application changes
- Even, edge-to-edge adhesive application
- Environmentally friendly



Product Specifications

Footprint	26.7cm x 33cm x 38.1cm
Weight/Packed Weight	6.6kg / 8.2kg
Document Thickness (max.)	3.2mm
Finished Document Width (max.)	30.5cm
Power Requirements	None
Cutter	Removable, replaceable cutter

The XM1255 is your complete professional document finishing system. Instantly applies laminate, adhesive or both without heat or electricity. Perfect for presentations, comps, packaging mock-ups, signs, displays and short-run labels.



Product Supply Description

Permanent High-Tack Adhesive: Aggressive adhesive instantly creates a permanent bond on most surfaces. Sets instantly and will not peel. Acid-Free.

Permanent Standard Adhesive: Moderately aggressive adhesive creates a permanent bond on most surfaces. Can be touched to surface, peeled back quickly, and replaced. Acid-Free.

Repositionable Adhesive: Allows items to be repositioned over and over. Easy removal from glass, walls, paper, and most other surfaces. Acid-Free.

Standard Use Laminate: A high gloss film suitable for use on a variety of substrates. Superior adhesion. Compatible with most media. Acid-Free.

Combination — Laminate/Adhesive: Laminate top surface to protect the document and adhesive on the bottom surface. Acid-Free

Product Supply Specifications

Part Number	Product Description	Material Length	Material Width	Laminate & Adhesive Combination Thickness (per side)	Mounting Adhesive Thickness	Adhesive pH	Mounting Adhesive Strength (1:10; 10-high)	PAT Approved
Adhesive Application Cartridges								
23621	Permanent High-Tack	30.5m	30.5cm	N/A	15.2mic	Acid-Free	10	Yes
23623	Permanent Standard	30.5m	30.5cm	N/A	15.2mic	Acid-Free	8	Yes
23624	Repositionable	30.5m	30.5cm	N/A	27.9mic	Acid-Free	3	Yes
Laminate Cartridges								
125115	2-Sided Standard Use Laminate	45.7m	30.5cm	67.5mic	N/A	Acid-Free	N/A	Yes
Combination One Side Laminate / One Side Adhesive Application Cartridges								
23625	1 Side Standard Use Laminate 1 Side High-Tack Adhesive	30.5m	30.5cm	67.5mic	15.2mic	Acid-Free	10	Yes
23626	1 Side Standard Use Laminate 1 Side Repositionable Adhesive	30.5m	30.5cm	67.5mic	27.9mic	Acid-Free	3	Yes

www.esselte.com

Your Authorized Xyron Dealer

