

## Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13

### AP9565

Call for More Information 0800 2799254



- Reliable rack power distribution designed to increase manageability and efficiency in the data center. The output and input connections are (12)C13. Real-time remote monitoring of connected loads. User-defined alarms warn IT and data center managers of potential circuit overloads to prevent accidental power loss to critical equipment.
- Includes: Installation guide, Rack mounting brackets

#### Output

Nominal Output Voltage	208V, 230V
Maximum Total Current Draw	16
Output Connections	(12) IEC 60320 C13

#### Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Cord Length	2.5meters
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

#### Physical

Maximum Height	44MM, 4.4CM
Maximum Width	447MM, 44.7CM
Maximum Depth	57MM, 5.7CM
Rack Height	1U
Net Weight	2.05KG
Shipping weight	3.63KG
Shipping Height	70MM, 7.0CM
Shipping Width	464MM, 46.4CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Rack PDU, Basic, 1U, 16A, 208/230V, (12)C13 | AP9565 | Downloaded on 11/01/2022 (EST)

Physical	
Shipping Depth	229MM, 22.9CM
Color	Black

Environmental	
Operating Temperature	0 - 45 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, cUL listed, Queensland Australia, UL 60950, UL listed, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.