



## APC Rack PDU 9000 Switched, ZeroU, 32A, 230V, (21) C13 & (3) C19

New

APDU9953

Call for More Information 0800 2799254

- Includes: Installation guide, Rack mounting brackets, Safety guide

### Output

Overload Protection	Yes
Maximum Total Current Draw	32
Output Connections	(21) IEC 60320 C13 (3) IEC 60320 C19

### Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 32 A 2P + E
Cord Length	3.1meters
Acceptable Input Voltage	220 - 240VAC
Number of Power Cords	1
Load Capacity	7400VA
Maximum Input Current	32A
Maximum Line Current	32A

### Physical

Maximum Height	1829MM, 182.9CM
Maximum Width	56MM, 5.6CM
Maximum Depth	46MM, 4.6CM
Net Weight	7.34KG
Shipping weight	9.95KG

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Physical	
Shipping Height	2040MM, 204.0CM
Shipping Width	124MM, 12.4CM
Shipping Depth	165MM, 16.5CM
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	-5 - 60 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	EAC, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, RCM, VDE
Standard warranty	3 years repair or replace

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.