



Rack PDU 2G, Metered, ZeroU, 32A, 230V, (36) C13 & (6) C19

AP8853

Call for More Information 0800 2799254

- APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. The output and input connections are (36) C13 & (6) C19, and the cable length is 3m. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower the total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra-low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
- Includes: Installation guide, Rack mounting brackets, Safety guide, Serial configuration cable

Output	
Nominal Output Voltage	230V
Overload Protection	Yes
Maximum Total Current Draw	32
Output Connections	(36) IEC 60320 C13 (6) IEC 60320 C19

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60309 32 A 2P + E
Cord Length	3meters
Acceptable Input Voltage	220 - 240VAC
Number of Power Cords	1
Load Capacity	7400VA
Maximum Input Current	32A
Maximum Line Current	32A

Physical	
Maximum Height	1791MM, 179.1CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Maximum Width	56MM, 5.6CM
Maximum Depth	44MM, 4.4CM
Net Weight	6.93KG
Shipping weight	8.56KG
Shipping Height	2000MM, 200.0CM
Shipping Width	107MM, 10.7CM
Shipping Depth	162MM, 16.2CM
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	-5 - 60 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	IEC 60950, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.