



## Rack PDU,Basic, Zero U, 16A, 230V, (20) C13 & (4) C19; IEC C20

AP7552

Call for More Information 0800 2799254

- Includes: Installation guide, Rack mounting brackets, Toolless mounting kit

Output	
Nominal Output Voltage	230V
Maximum Total Current Draw	16
Output Connections	(20) IEC 60320 C13 (4) IEC 60320 C19

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Cord Length	3.1meters
Number of Power Cords	1
Load Capacity	3680VA
Maximum Input Current	16A

Physical	
Maximum Height	1619MM, 161.9CM
Maximum Width	56MM, 5.6CM
Maximum Depth	44MM, 4.4CM
Net Weight	4.86KG
Shipping weight	5.76KG
Shipping Height	2121MM, 212.1CM
Shipping Width	152MM, 15.2CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Physical	
Shipping Depth	127MM, 12.7CM
Color	Black

  

Environmental	
Operating Temperature	0 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

  

Conformance	
Approvals	CE, GOST, IRAM, VDE
Standard warranty	2 years repair or replace

  

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.