



Power Cord, C13 to C14, 2.5m
Part Number: AP9870



Output

Maximum Total Current Draw per Phase
10A
Output Connections
(1) IEC 320 C13



Overload Protection
No

Input

Input Frequency
50/60 Hz
Input Connections
IEC-320 C14
Cord Length
2.5 meters
Number of Power Cords
1
Acceptable Input Voltage
90-250 VAC
Maximum Line Current per phase
10A
Maximum Input Current per phase
10A

Physical

Net Weight
0.23 KG
Maximum Height
38.00 mm
Maximum Width
76.00 mm
Maximum Depth
203.00 mm
Shipping Weight
0.30 KG
Shipping Height
51.00 mm
Shipping Width
102.00 mm
Shipping Depth
203.00 mm
Color
Black
Units per Pallet
600.00

Environmental

Operating Environment
0 - 45 °C
Operating Relative Humidity
0 - 95%
Operating Elevation

0-3000 meters
Storage Temperature
-25 - 65 °C
Storage Relative Humidity
0 - 95%
Storage Elevation
0-15000 meters

Conformance

Regulatory Approvals
CSA,UL Listed,VDE
Standard Warranty
2 years repair or replace
Environmental Compliance
RoHS

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[About Schneider Electric](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)