



BEESWIFT®
FOCUSED ON SAFETY

Product Code:

CARC28

Selling UOM:

Each

Pack Size:

1



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant

SPECIFICATION SHEET

ARC COMPLIANT BALACLAVA



- Flame Retardant, Anti-Static, ARC Flash Balaclava hood.
- 210gsm 60/40 Modacrylic/ cotton with anti static.
- Inherently flame retardant fabric.
- FR properties will not diminish with repeated laundering
- Soft comfortable fabric with contrast FR sewing thread

EN ISO 13688: 2013
EN 1149-3: 2004
EN 1149-5: 2008
EN ISO 11612: 2015 (A1 B1 C1)
EN ISO 14116: 2015 (3/5H/40)

IEC 61482-2-2009
EN 61482-1-2-2007 (Class 1 = 4 kA) - Box Arc testing
EN 61482 - 1 - 1 : 2009 (EBT50 = 5.9 cAL/cm2) Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	660.00	328.00	304.00	486.00
Cardboard	Inner	20	40.16	246.00	156.00	620.00
Paper	Inner	20	33.90			
Cardboard	Inner	2	58.68			
Carton Weight:		4.26kg				