

An affordable easy to use laser display solution with wireless connectivity and built-in speakers

Bring sharp images and bright colours to any meeting room with our super-bright new business projector combined with HD-ready WXGA resolution. The EB-L210W is designed to stream and share with wireless LAN, Screen Mirroring and split screen with two or four inputs in one display.

Outstanding quality

WXGA compact laser display with high contrast ratio of 2,500,000:1 and 3LCD technology provides pin-sharp image quality and equally high white and colour light output give your presentations impact, even in brightly-lit rooms.

Simple set-up and connectivity

Offers MTR auto power-on function by HDMI video signal detection and an array of connectivity options including Dual HDMI and built-in wireless LAN to stream content from laptops or mobile devices with Screen Mirroring (Miracast) - PIN code support and display dialog username when connected Miracast to projector allows teacher to block student interruption while teacher is projecting. USB power supply (2A) for easy smart stick connection. Compatible with iProjection software for easy connectivity with mobile devices and content sharing.

Peace of mind and long-lasting durability

Project for longer with exceptional reliability and a longer usage life of up to 30,000 hours in Eco Mode (20,000 hours normal). The EB-L210W is covered by a five-year warranty.

Value added flexibility

Epson iProjection software is compatible with leading platforms and makes it possible to connect with up to 50 computers and partition the screen for split-screen projection capability offering added value.

DATASHEET / BROCHURE



KEY FEATURES

• **4,500 lumens brightness display** Crisp images and bright colours, even in well-lit rooms.

Laser projector

Virtually maintenance-free performance for up to 30,000 hours (Eco).

• Stream and share Wireless, MTR auto power-on by HDMI

and easy smart stick connection.

• Fit and forget reliability

Flexible, compact laser projector, comes with five-year warranty.

• The complete solution

With an incredible contrast ratio of 2,500,000:1, the EB-L210W delivers vivid, lifelike content and defined shadow detail with deeper blacks.

Legal Statement

Complies with The UK Product Security and Telecommunications Infrastructure (Product Security) requirements. Epson will provide security updates for 7 years from purchase



PRODUCT SPECIFICATIONS

TECHNOLOGY	
Projection System	3LCD Technology, RGB liquid crystal shutter
LCD Panel	0.59 inch with C2 Fine
IMAGE	
Color Light Output	4,500 Lumen- 3,100 Lumen (economy) In accordance with IDMS15.4
White Light Output	4,500 Lumen - 3,100 Lumen (economy) In accordance with ISO 21118:2020
Resolution	WXGA
High Definition	HD ready
Aspect Ratio	16:10
Pixel Numbers	1,024,000
Contrast Ratio	5,000,000 : 1
Light source	Laser
Laser Light source	20,000 hours Durability High, 30,000 hours Durability Eco
Keystone Correction	Auto vertical: ± 30 °, Manual horizontal ± 30 °
2D Vertical Refresh Rate	100 Hz - 120 Hz
Colour Reproduction	Upto 1.07 billion colours
0071041	
OPTICAL	1 41 0 06.1
Throw Ratio Zoom	1.41 - 2.26:1 Manual Factor: 1 - 1.62
	Manual, Factor: 1 - 1.62 1.41 - 2.26 : 1
Projection Lens Zoom Ratio	
Lens Screen Size	Optical 30 inches - 300 inches
Screen Size Projection Distance Wide	30 inches - 300 inches 0.9 m - 9.1 m
Projection Distance wide Projection Lens F Number	0.9 m - 9.1 m 1.51 - 1.77
Projection Lens F Number Projection Lens Focal Length	
Projection Lens Focus Offset	Manual 10:1
onset	
CONNECTIVITY	
Interfaces	USB 2.0-A, USB 2.0, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN a/n
	(5GHz), Wi-Fi Direct, VGA in (2x), VGA out, Composite in, Miracast, Jack plug out, Jack plug in
	(2x), Cinch audio out, Microphone input, HDMI (HDCP 2.2) (2x)
Epson iProjection App	Ad-Hoc / Infrastructure
Network Protocol	HTTPS, IPv6, SNMP, PJLink
ADVANCED FEATURES	
Security	Kensington lock, Padlock, Security cable hole, Wireless LAN unit lock
2D Colour Modes	Dynamic, Cinema, Presentation, sRGB, Blackboard
Other features	AV Mute Slide, Auto Power On, Built-in speaker, CEC compatible, Document Camera
	Compatible, Home Screen, Long light source life, Mute key, OSD copy function, PC Free,
	Quick Corner, Screen Mirroring, Split-Screen-Function, Wireless LAN capable, iProjection App
Video Color Modes	Cinema, Dynamic, Presentation, sRGB
Projector control	
	via: Crestron Integrated Partner, Extron IP Link, AMX Device Discovery, Control4 Simple
	via: Crestron Integrated Partner, Extron IP Link, AMX Device Discovery, Control4 Simple Device Discovery Protocol
GENERAL	Device Discovery Protocol
GENERAL	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199
GENERAL Power consumption	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby)
GENERAL Power consumption Supply Voltage	201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz
GENERAL Power consumption Supply Voltage Product dimensions	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height)
GENERAL Power consumption Supply Voltage Product dimensions Product weight	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A)
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90%
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity ncluded Software	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker,
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Loudspeaker	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01 16 Watt
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01 16 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application Positioning	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01 16 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom Ceiling Mounted, Desktop
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01 16 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application Positioning	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01 16 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom Ceiling Mounted, Desktop
GENERAL Power consumption Supply Voltage Product dimensions Product weight Noise Level Supported Temperature Supported Humidity Included Software Options Loudspeaker Room Type / Application Positioning Colour	Device Discovery Protocol 201 Watt (Normal On-Mode), 144 Watt (Eco On-Mode), 260 Watt (Normal Peak-mode), 199 Watt (Eco Peak-Mode), 0.5 Watt (Energy saving standby) AC 220 V - 240 V, 50 Hz - 60 Hz 325 x 299 x 90 mm (Width x Depth x Height) 4.2 kg Normal: 37 dB (A) - Economy: 27 dB (A) Storage -10° C - 60° C Operation 20% - 80%, Storage 10% - 90% Epson Projector Management Air filter, Ceiling mount, Connection and control box, Document camera, External Speaker, Soft carry case, Suspension adapter, WP System - ELPWP10, Wireless transmitter - ELPWT01 16 Watt Boardroom, Home Office, Large Meeting Room / Auditorium, Meeting room / Classroom Ceiling Mounted, Desktop

Epson EB-L210W

WHAT'S IN THE BOX

• Remote control incl. batteries

EPSON[®]

- Power cable
- Main unit
- HDMI Cable 1.8m

OPTIONAL ACCESSORIES

- Soft Carry Case ELPKS71 V12H001K71
- Air Filter ELPAF60 EB-7XX / EB-L2xx Series V13H134A60
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- Active Speakers (2 x 15W) ELPSP02 V12H467040DA
- Control and Connection Box ELPCB03 V12H927040DA
- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Lighting Track Mount ELPMB61W V12H964240
- Ceiling mount / Floor stand ELPMB60W V12H963210

LOGISTICS INFORMATION

SKU	V11HA70080
EAN code	8715946715476
Country of Origin	Philippines
Layer	4 Units
Layer Block	6 Units

Wireless Presentation Systems

- Epson ELPWP10 Wireless Presentation System V12HA41040
- Epson ELPWP20 Wireless Presentation System V12HA42040

Visualizers

- ELPDC30
- V12HB09080
- ELPDC07
 V12H759040
- ELPDC13
- V12H757040DA
- ELPDC21
 V12H758040DA

Web: www ww

Business users*: 0871 42 37766 Republic of Ireland: 01 436 7742 Or visit us at https://www.epson.co.uk/contactus * 10p per minute plus network extras. eb: www.epson.co.uk www.epson.ie Epson EB-L210W



1. - Requires iProjection App and an internet connection - compatible with iOS, Android and Google Chromebook

devices only, and file sharing limitations may apply.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice. Last extracted: 2023-05-15