

INK PERMACHROME NAVY - PR3100

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : INK PERMACHROME NAVY

Product code : PR3100.

1.2. Relevant identified uses of the substance or mixture and uses advised against

SHARPIE : Ultra fine

1.3. Details of the supplier of the safety data sheet

Registered company name : Newell Rubbermaid UK Limited.

Address : Halifax Ave - Fradley Park .WS 13 8SS.Lichfield Staffordshire.United Kingdom.

Telephone : +44 (0) 1543447001. Fax : .

Aftersales.SERVICE@newellco.com

www.newellrubbermaid.com

1.4. Emergency telephone number : 0845 4647.

Association/Organisation : National Poisons Information Service.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Acute dermal toxicity, Category 2 (Acute Tox. 2, H310).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Flammable (R 10).

Skin irritation (Xi, R 38).

Serious eye damage (Xi, R 41).

Vapours may cause drowsiness and dizziness (R 67).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS06



GHS05



GHS02

Signal Word :

DANGER

INK PERMACHROME NAVY - PR3100

Product identifiers :

603-003-00-0 PROPAN-1-OL
603-004-00-6 N-BUTANOL
EC 206-056-4 BIS(2-ETHYLHEXYL)HYDROGEN PHOSPHATE

Additional labeling :

Hazard statements :

H226 Flammable liquid and vapour.
H310 Fatal in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 Ground/bond container and receiving equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P262 Do not get in eyes, on skin, or on clothing.
P264 Wash ... thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :

P302 + P352 IF ON SKIN: Wash with plenty of water/...
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/...
P312 Call a POISON CENTER/doctor/.../if you feel unwell.
P321 Specific treatment (see ... on this label).
P361 + P364 Take off immediately all contaminated clothing and wash it before reuse.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use... to extinguish.

Precautionary statements - Storage :

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary statements - Disposal :

P501 Dispose of contents/container to ...

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

INK PERMACHROME NAVY - PR3100

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 603-003-00-0 CAS: 71-23-8 EC: 200-746-9 PROPAN-1-OL	GHS02, GHS05, GHS07 Dgr Flam. Liq. 2, H225 Eye Dam. 1, H318 STOT SE 3, H336	Xi,F Xi;R41 F;R11 R67	[1]	25 <= x % < 50
INDEX: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 N-BUTANOL	GHS02, GHS05, GHS07 Dgr Flam. Liq. 3, H226 Acute Tox. 4, H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336	Xn Xn;R22 Xi;R37/38-R41 R10 R67	[1]	10 <= x % < 25
INDEX: 603-016-00-1 CAS: 123-42-2 EC: 204-626-7 DIACETONE ALCOHOL	GHS07 Wng Eye Irrit. 2, H319	Xi Xi;R36	[1]	10 <= x % < 25
CAS: 298-07-7 EC: 206-056-4 BIS(2-ETHYLHEXYL)HYDROGEN PHOSPHATE	GHS07, GHS05 Dgr Acute Tox. 4, H312 Skin Corr. 1B, H314 Aquatic Chronic 3, H412	C C;R34 Xn;R21 R52/53		0 <= x % < 2.5

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
 NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.
 If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.
 If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
 Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
 Remove any soiled or splashed clothing immediately.
 Watch out for any remaining product between skin and clothing, watches, shoes, etc.
 If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

INK PERMACHROME NAVY - PR3100

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

INK PERMACHROME NAVY - PR3100

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture at all times.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

INK PERMACHROME NAVY - PR3100

Storage

Keep out of reach of children.
Keep the container tightly closed in a dry, well-ventilated place.
Keep away from all sources of ignition - do not smoke.
Keep well away from all sources of ignition, heat and direct sunlight.
Avoid accumulation of electrostatic charges.
The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
71-23-8	200 ppm	400 ppm	-	-	-
71-36-3	20 ppm	-	-	-	-
123-42-2	50 ppm	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
71-36-3	100 ml/m3	310 mg/m3	1(I)	DFG, Y
123-42-2	20 ml/m3	96 mg/m3	2(I)	DFG, H

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
71-23-8	200	500	-	-	-	84
71-36-3	-	-	50	150	-	84
123-42-2	50	240	-	-	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
71-23-8	200 ppm	250 ppm	-	-	-
71-36-3	-	50 ppm	-	-	-
123-42-2	50 ppm	75 ppm	-	-	-

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles with protective sides accordance with standard EN166.
In the event of high danger, protect the face with a face shield.
Prescription glasses are not considered as protection.

INK PERMACHROME NAVY - PR3100

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.
Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Important health, safety and environmental information

pH :	Not relevant.
Boiling point/boiling range :	Not specified.
Flash Point :	28.00 °C.
Explosive properties, lower explosivity limit (%) :	2.2 Vol. %
Explosive properties, upper explosivity limit (%) :	14 Vol. %
Vapour pressure (50°C) :	Not relevant.
Density :	Not stated.
Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

INK PERMACHROME NAVY - PR3100

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Fatal in contact with skin.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

Acute toxicity :

BIS(2-ETHYLHEXYL)HYDROGEN PHOSPHATE (CAS: 298-07-7)

Oral route :

LD50 = 4.94 ml/kg

Species : Rat (recommended by the CLP)

Dermal route :

LD50 = 1.25 ml/kg

Species : Rabbit (recommended by the CLP)

11.1.2. Mixture

No toxicological data available for the mixture.

INK PERMACHROME NAVY - PR3100

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

BIS(2-ETHYLHEXYL)HYDROGEN PHOSPHATE (CAS: 298-07-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK) :

WGK 1 (VwVwS vom 27/07/2005, KBws) : Slightly hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

08 01 13 * sludges from paint or varnish containing organic solvents or other dangerous substances

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

14.1. UN number

3175

14.2. UN proper shipping name

UN3175=SOLIDS or mixtures of solids (such as preparations and wastes) CONTAINING FLAMMABLE LIQUID, N.O.S. having a flash-point up to 60 °C

INK PERMACHROME NAVY - PR3100

14.3. Transport hazard class(es)

- Classification :



4.1

14.4. Packing group

II

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	4.1	F1	II	4.1	40	1 kg	216 274 601	E2	2	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	4.1	-	II	1 kg	F-A,S-I	216 274	E2

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	4.1	-	II	445	15 kg	448	50 kg	A46	E2
	4.1	-	II	Y441	5 kg	-	-	A46	E2

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

- Container information:

The mixture is contained in packaging that does not exceed 125 ml.

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK) :

WGK 1 (VwVwS vom 27/07/2005, KBws) : Slightly hazardous for water.

15.2. Chemical safety assessment

No data available.

INK PERMACHROME NAVY - PR3100

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :



Irritant

Flammable

Contains :

603-003-00-0

PROPAN-1-OL

603-004-00-6

N-BUTANOL

Risk phrase :

R 38

Irritating to skin.

R 10

Flammable.

R 41

Risk of serious damage to eyes.

R 67

Vapours may cause drowsiness and dizziness.

Safety phrase :

S 1/2

Keep locked up and out of the reach of children.

S 26

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 36/39

Wear suitable protective clothing and eye/face protection.

S 45

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S 46

If swallowed, seek medical advice immediately and show this container or label.

S 25

Avoid contact with eyes.

S 28

After contact with skin, wash immediately with plenty of ... (to be specified by the manufacturer).

S 37

Wear suitable gloves.

S 51

Use only in well-ventilated areas.

S 64

If swallowed, rinse mouth with water (only if the person is conscious).

S 7

Keep container tightly closed.

S 20

When using do not eat or drink.

S 24

Avoid contact with skin.

Title for H, EUH and R indications mentioned in section 3 :

H225

Highly flammable liquid and vapour.

H226

Flammable liquid and vapour.

H302

Harmful if swallowed.

H312

Harmful in contact with skin.

H314

Causes severe skin burns and eye damage.

H315

Causes skin irritation.

H318

Causes serious eye damage.

INK PERMACHROME NAVY - PR3100

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
R 10	Flammable.
R 11	Highly flammable.
R 21	Harmful in contact with skin.
R 22	Harmful if swallowed.
R 34	Causes burns.
R 36	Irritating to eyes.
R 37/38	Irritating to respiratory system and skin.
R 41	Risk of serious damage to eyes.
R 52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 67	Vapours may cause drowsiness and dizziness.

Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS05 : Corrosion

GHS06 : Skull and crossbones