# **PRODUCT SAFETY DATA SHEET**



#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

AIR WICK Pure Freshmatic Compact Spring Delight

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

For fragrancing and ambience / mood creation

#### 1.3. Details of the Supplier of the Safety Data Sheet

The United Kingdom:
RB UK Commercial Ltd

Wellcroft House

Wellcroft Road

Slough Berkshire

SL1 4AQ

The Republic Of Ireland:

Reckitt Benckiser Ireland Ltd

7 Riverwalk

Citywest Business Campus

Dublin 24 Ireland

1.4 Emergency telephone number Only available during the following office hours: 09:00 - 17:00 weekdays

UK Contact Telephone: 0845 769 7079 ROI Contact Telephone: 01 661 7318

Contact Email: consumer.relations-ukroi@rb.com

Revision Date:RevisionReplacingRB Ref No:1 December 201510165163801

**Revisions:** New product

Additional useful information

Product Format: Aerosol can in plastic sleeve with plastic device

UN Transport Code UN: 1950

Class & Packing Group 2.1

Proper Shipping Name Aerosols

Store below 50°C

**(i**)



#### **SECTION 2: HAZARDS IDENTIFICATION**

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Aerosol 1, H222

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : F+; R12

R52/53

Physical/chemical :

hazards

: Extremely flammable.

Environmental hazards : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :

**③** 

Signal word : Danger

Hazard statements : Extremely flammable aerosol.

Precautionary statements

General : Keep out of reach of children.

If medical advice is needed, have product container or label at hand.

Use only as directed

Prevention : Pressurized container: may burst if heated.

Protect from sunlight and do not expose to temperatures exceeding 50 °C.

Do not pierce or burn, even after use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking

Do not spray on an open flame or other ignition source.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Storage : Not applicable.

Disposal : Not applicable.

Hazard symbol or symbols



Indication of danger : Extremely flammable

Risk phrases : R12- Extremely flammable.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S2- Keep out of the reach of children.

S16- Keep away from sources of ignition - No smoking.

S23- Do not breathe spray. S25- Avoid contact with eyes.

S26- In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S46- If swallowed, seek medical advice immediately and show this container or

label.

S51- Use only in well-ventilated areas.



Hazardous ingredients

(DPD)

Hazardous ingredients

(CLP)

: Not applicable.

: Not applicable.

Supplemental label elements (DPD)

: Contains 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone. Butlphenyl methylpropional, alpha-iso-Methylionone, p-tert-Butyldihydrocinnamaldehyde, dl-Limonene and dl-Citronellol. May produce an allergic reaction. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition No smoking. Keep out of the reach of children.

Supplemental label elements (CLP)

: Contains 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone. Butylphenyl methylpropional, alpha-iso-Methylionone, p-tert-Butyldihydrocinnamaldehyde, dl-Limonene and dl-Citronellol. May produce an allergic reaction. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition No smoking. Keep out of the reach of children.

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

Recommendations

: People suffering from perfume sensitivity should be cautious when using this product. Air Fresheners do not replace good hygiene practices.



## **SECTION 3: Composition/Information on Ingredients**

Substance/mixture : Mixture

			Classification		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Butane	EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	30 - 60	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Isobutane	EC: 200-857-2 CAS: 75-28-5 Index: 601-004-00-0	15 - 30	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
propane	EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	15 - 30	F+; R12	Flam. Gas 1, H220 Press. Gas, H280	[2]
Distillates (petroleum), hydrotreated light	EC: 265-149-8 CAS: 64742-47-8 Index: 649-422-00-2	< 2.5	Xn; R65	Asp. Tox. 1, H304	[1]
1-(1,2,3,4,5,6,7, 8-octahydro-2,3,8, 8-tetramethyl- 2-naphthyl)ethan-1-one	EC: 259-174-3 CAS: 54464-57-2	0.25 - 1	Xi; R38 R43 N; R51/53	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
2-(4-tert-butylbenzyl) propionaldehyde	EC: 201-289-8 CAS: 80-54-6	< 0.25	Repr. Cat. 3; R62 Xn; R22 Xi; R38 R43 N; R51/53	Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361fd (Fertility and Unborn child) Aquatic Chronic 2, H411	[1]
3-methyl-4-(2,6, 6-trimethyl- 2-cyclohexen-1-yl) -3-buten-2-one	EC: 204-846-3 CAS: 127-51-5	< 0.25	R43 N; R51/53	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
3-(4-tert-butylphenyl) propionaldehyde	EC: 242-016-2 CAS: 18127-01-0	< 0.25	Repr. Cat. 3; R62 Xn; R22 R43 N; R51/53	Acute Tox. 3, H301 Skin Sens. 1, H317 Repr. 2, H361fd (Fertility and Unborn child)	[1]
dipentene	EC: 205-341-0 CAS: 138-86-3 Index: 601-029-00-7	< 0.25	R10 Xi; R38 R43 N; R50/53	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 1, H410	[1]
citronellol	EC: 203-375-0 CAS: 106-22-9	< 0.25	Xi; R38 R43 N; R51/53	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317	[1]
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.



#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

#### Type

- [f] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.



#### **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery

position and get medical attention immediately. Maintain an open airway.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion: Wash out mouth with water. Remove dentures if any. Move to fresh air. If material

has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery

position and get medical attention immediately. Maintain an open airway.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Freat symptomatically.

Specific treatments : No specific treatment.



#### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.



## **SECTION 7: HANDLING AND STORAGE**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

#### Protective measures

: Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous

## Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

#### 7.3 Specific end use(s)

Recommendations

: Air care products

Consumer uses: Private households (= general public = consumers)

Industrial sector specific solutions

Not available.



#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

#### Occupational exposure limits

Exposure limit values
EU OEL (Europe, 7/2012). Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits
TWA: 800 ppm 8 hours.
TWA: 1900 mg/m³ 8 hours.
EU OEL (Europe, 1/2012).
TWA: 1000 ppm 8 hours. Form: gas
EU OEL (Europe, 5/2010). Oxygen Depletion [Asphyxiant]. OELV-8hr: 1000 ppm 8 hours.

## procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## 8.2 Manufacturer: Exposure controls

#### Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosionproof ventilation equipment.

#### Individual protection measures

#### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

## Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately

Permeation level 6, Penetration level 3 following EN374, taking into consideration the exposure of chemicals given in chapter 3.



#### **Body protection**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

#### Other skin protection

 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.



## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Aerosol.]

Colour : Colourless to light yellow.

Odour : Characteristic. Odour threshold : Not available. pΗ : Not available. Melting point/freezing point : Not available.

Initial boiling point and

boiling range

: <34°C

Flash point : Closed cup: <0°C : Not available. Evaporation rate : Not available. Flammability (solid, gas) **Burning time** : Not applicable. : Not applicable. **Burning rate** 

Upper/lower flammability or

explosive limits

: Not available.

Vapour pressure : Not available. Vapour density : Not available. : Not available. Density : Not available. Solubility(ies) Partition coefficient: n-octanol/ : Not available.

water

Decomposition temperature : Not available. : Not available. Viscosity : Not available. **Explosive properties** : Not available. Oxidising properties : Not available. Corrosivity Remarks

9.2 Other information

Aerosol product

Type of aerosol : Spray : 41.6 kJ/g Heat of combustion

No additional information.



## **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. Polymerisation. : There are no data available on the mixture itself.

10.4 Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials : Do not mix with household chemicals

10.6 Hazardous decomposition products

: Hazardous decomposition products : carbon oxides , Various Organic chemicals.

Instability Conditions : Not available.

Instability temperature : Not available.



## **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name Result		Species	Dose	Exposure
<b>B</b> utane	LC50 Inhalation Vapour	Rat	658000 mg/m³	4 hours
Isobutane	LC50 Inhalation Vapour	Rat	658000 mg/m <sup>3</sup>	4 hours
2-(4-tert-butylbenzyl) propionaldehyde	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	1390 mg/kg	-
3-methyl-4-(2,6,6-trimethyl-	LD50 Dermal	Rabbit	>5000 mg/kg	-
2-cyclohexen-1-yl)-3-buten- 2-one				
	LD50 Oral	Rat	>5000 mg/kg	-
3-(4-tert-butylphenyl) propionaldehyde	LD50 Oral	Rat	2700 mg/kg	-
dipentene	LD50 Oral	Rat	5300 mg/kg	-
citronellol	LD50 Dermal	Rabbit	2650 mg/kg	-
	LD50 Oral	Rat	3450 mg/kg	-

## Acute toxicity estimates

Route	ATE value
<b>O</b> ral	65424.9 mg/kg

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-(4-tert-butylbenzyl) propionaldehyde	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
dipentene	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
citronellol	Eyes - Moderate irritant	Rabbit	-	0.42 Percent	-
	Skin - Severe irritant	Guinea pig	-	24 hours 100 milligrams	-
	Skin - Moderate irritant	Man	-	48 hours 16 milligrams	-
	Skin - Moderate irritant	Rabbit	-	4 hours 0.42 Percent	-
	Skin - Severe irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin - Severe irritant	Rabbit	-	4 hours 0.5 Mililiters	-

## Sensitisation

No known effect according to our database.

#### Mutagenicity

No known effect according to our database.

#### Carcinogenicity

No known effect according to our database.

#### Reproductive toxicity

No known effect according to our database.

## **Teratogenicity**

No known effect according to our database.

## Specific target organ toxicity (single exposure)

No known effect according to our database.

## Specific target organ toxicity (repeated exposure)

No known effect according to our database.



#### Aspiration hazard

Product/ingredient name	Result
Distillates (petroleum), hydrotreated light dipentene	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

## Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.
Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Other information : Not available.



## **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated light	Acute LC50 2200 μg/l Fresh water	Fish - Lepomis macrochirus	4 days
dipentene			48 hours 96 hours

#### 12.2 Persistence and degradability

No known effect according to our database.

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Butane	2.89	-	low
Isobutane	2.8	-	low
propane	2.36	-	low
dipentene	4.57	-	high
citronellol	3.41	82.59	low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc) Not available.

Mobility (Koc)

Not available.

## 12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### Product

Methods of disposal

 Waste must be disposed of in accordance with federal, state and local environmental control regulations. Waste packaging should be recycled.

Hazardous waste Packaging : The classification of the product may meet the criteria for a hazardous waste.

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.



## **SECTION 14: TRANSPORT INFORMATION**

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1950	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2	2	2.1	2.1
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	<b>Y</b> es.	No.	No.
Additional information	Limited quantity	Emited quantity	Limited quantity	See DG List



## **SECTION 15: REGULATORY INFORMATION**

Chemical Safety Assessment following regulation 1907/2006/EC: Not relevant.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain

dangerous substances, mixtures and articles

Integrated pollution prevention and control : Not listed

list (IPPC) - Air Integrated pollution

prevention and control list (IPPC) - Water : Not listed

:

## **CMR Substances**

Product/ingredient name	Carcinogenic effects	Mutagenic effects	Developmental effects	Fertility effects
2-(4-tert-butylbenzyl) propionaldehyde 3-(4-tert-butylphenyl) propionaldehyde	-	-	(Unborn child) Repr. 2, H361d	Repr. 2, H361f (Fertility) Repr. 2, H361f (Fertility)

Aerosol dispensers

\*

Extremely flammable

Hazard class for water

: 2 Appendix No. 4

15.2 Chemical Safety Assessment : Not applicable.



## **SECTION 16: OTHER INFORMATION**

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Key literature references and sources for data

: Not available.

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Aerosol 1, H222

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classif	ication	Justification		
Fam. Aerosol 1, H222		Expert judgment		
Europe Full text of abbreviated H statements	H301 Toxic if swallow H302 Harmful if swallow H304 May be fatal if s H315 Causes skin irrit H317 May cause an a H319 Causes serious H361fd Suspected of da (Fertility and Unborn child) H410 Very toxic to aqu	nable aerosol. id and vapour. ider pressure; may explode if heated. ed. owed. wallowed and enters airways. tation. Illergic skin reaction.		
Full text of classifications [CLP/GHS]	: Acute Tox. 3, H301 Acute Tox. 4, H302 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411 Asp. Tox. 1, H304 Eye Irrit. 2, H319 Flam. Aerosol 1, H222 Flam. Gas 1, H220 Flam. Liq. 3, H226 Press. Gas Comp. Gas, H280	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (oral) - Category 4 LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 2 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE AEROSOLS - Category 1 FLAMMABLE GASES - Category 1 FLAMMABLE LIQUIDS - Category 3 GASES UNDER PRESSURE - Compressed gas  TOXIC TO REPRODUCTION (Fertility and Unborn child) - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1		

Full text of abbreviated R phrases

: R12- Extremely flammable.

R10- Flammable.

R62- Possible risk of impaired fertility.

R22- Harmful if swallowed.

R65- Harmful: may cause lung damage if swallowed.

R38- Irritating to skin.

R43- May cause sensitisation by skin contact.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.



# Full text of classifications [DSD/DPD]

: F+ - Extremely flammable

Repr. Cat. 3 - Toxic to reproduction category 3

Xn - Harmful Xi - Irritant

N - Dangerous for the environment

This document complements the technical usage instructions but does not replace them. The information contained herein is based on our best current knowledge if the product concerned, and is given in good faith. The attention of recipients is drawn to (amongst other things) the element of risk consequent to use of the product other than that for which it was intended.

In no way does this document remove the need of the recipient of the product to fully understand and apply statutory requirements. It is the recipient's sole responsibility to take due precautions relative to the use made of the product. All information contained herein is only to assist the recipient in fulfilling their statutory duty connected with the use of hazardous materials.

This Document may be entitled <u>Product Safety Data Sheet</u> as required by REACH (Registration, Evaluation, Authorisation and restriction of Chemicals) Annex II OR <u>Product Data Information Sheet</u> where a product is not required to be supported by a full REACH compliant SDS (e.g. not classified as hazardous or out of scope, such as cosmetics). Changes from the previous version are given in Section 1.

This list of information must not be considered as exhaustive, and does not exonerate the recipient from taking other precautions described in documents other than those mentioned, concerning the storage and use of the product, for which they remain the sole person responsible.