



**BEESWIFT**<sup>®</sup>  
FOCUSED ON SAFETY

Product Code:

CARC6N42

Selling UOM:

Each

Pack Size:

1



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Protection for Welding and Allied Processes

# SPECIFICATION SHEET

## ARC COMPLIANT COVERALL NAVY 42



- Fire retardant, Anti-static, ARC Flash coverall.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 hip pockets.
- Rear patch pocket with hook and loop closure flap.
- Large bellows pocket to each leg with hook and loop closure flap.
- Right leg mobile phone pocket with hook and loop closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

EN ISO 13688:2013 - General requirements for protective clothing  
 EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay  
 EN 1149-5:2008 - Anti Static - Material performance and design requirements  
 EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding  
 EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

**ARC FLASH**  
 IEC 61482-2:2009 - Performance requirements and design requirements  
 EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing  
 EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm<sup>2</sup>) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.
- Does NOT conform to EN ISO 20471



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	980.00	580.00	400.00	284.00
Plastic	Inner	10	32.82			
Paper	Inner	10	8.09			
Cardboard	Inner	10	1.39			
<b>Carton Weight:</b>		15.78kg				