



BEESWIFT
FOCUSED ON SAFETY

Product Code:

CARC4N34T

Selling UOM:

Each

Pack Size:

1



Anti Static



Arc Flash Protection



Cat 3 - High Risk



Fire Retardant



Protection for Welding and Allied Processes

SPECIFICATION SHEET

ARC COMPLIANT TROUSER NAVY 34T



- Fire retardant, Anti-static, ARC Flash cargo style trousers.
- 300gsm 60/40 Modacrylic/cotton blend.
- Inherently flame retardant.
- Flame retardant qualities will not diminish during life of garment.
- Triple stitch construction.
- 7 belt loop part elastic waistband, double button closure.
- 2 hip pockets.
- Rear patch pocket with hook and loop closure flap.
- Large bellows pocket to each leg with hook and loop closure flap.
- Right leg mobile phone pocket with hook and loop closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.

Leg length:
Small (S) - 29"
Regular - 31"
Tall (T) - 33"

EN ISO 13688:2013 - General requirements for protective clothing
EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
EN 1149-5:2008 - Anti Static - Material performance and design requirements
EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements

EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing

EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm²) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.
- Does NOT conform to EN ISO 20471



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	1,040.00	578.00	404.00	332.00
Plastic	Inner	20	29.54			
Tissue Paper	Inner	20	1.27			
Paper	Inner	20	34.21			
Cardboard	Inner	2	60.10			
Cardboard	Inner	20	1.78			
Carton Weight:			17.44kg			