

## TWO TONE ARC WOVEN JACKET LGE



SPECIFICATION

Product Code:

CARC925SYNL

Selling UOM:

Each

Pack Size:

1





Arc Flash Protection



Cat 3 - High Risk Fire Retardant



Hi Visibility



Protection for Welding and Allied Processes

- Fire Retardant, Hi Vis, Anti-static, ARC Flash Jacket.
- 300gsm 60/40 Modacrylic/cotton blend.
- Triple stitch construction.
- 2 Lower pockets.
- Large qualifying icons on left arm.
- EN ISO 13688:2013 General requirements for protective clothing
- EN ISO 20471:2013 Class 3 Test method for high visibility
- EN 1149-3:2004 Anti Static Test methods for measurements of charge decay
- EN 1149-5:2008 Anti Static Material performance and design requirements

• EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding

• EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

## ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements

EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing EN 61482-1-1:2009 (ATPV = 10.8 Cal/cm2) - Open Arc testing

- Each garment style is independently tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Packaging Waste	Туре	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	1.040.00	550.00	414.00	236.00
Cardboard	Inner	10	1.28			
Plastic	Inner	10	32.55			
Paper	Inner	10	22 84			

11.04kg

Carton Weight: