



SPECIFICATION SHEET

GLOVEZILLA TITAN ARMOUR NEEDLESTICK GLOVE BLUE SML



Product Code:
GZ67BS

Selling UOM:
Pair
Pack Size:
1

FEATURES

- Dependable grip, excellent flexibility and a comfortable ergonomic shape.
- Puncture-resistant with latex coating
- Lined with two layers of Titan Armour
- Makes a great general-purpose work glove
- ASTM F2878 14.4 newtons of puncture protection (hypodermic needle)
- EN388: 2016
- Level 2 - Abrasion
- Level X - Cut Resistance (Coupe Test)
- Level 4 - Tear Resistance
- Level 4 - Puncture
- Level F - ISO 13997 Cut Resistance

- EN 407: 2004
- Level X - Burning Behaviour
- Level 2 - Contact Heat
- Level X - Convective heat
- Level X - Radiant heat
- Level X - Small splashes of Molten Metal
- Level X - Large splashes of Molten Metal

• Please note: there is no European standard for needle resistance. Current industry practice is to utilize the American Standard ASTM F2878 as a guide, and to allow comparisons between different products. These products are not needle proof. Your own risk assessment therefore needs to be undertaken to decide the suitability of this product.



| Packaging Waste | Type | Units | Weight(g) | Length(mm) | Width(mm) | Height(mm) |
|-----------------------|--------|-------|-----------|------------|-----------|------------|
| Cardboard | Inner | 40 | 9.79 | | | |
| Paper | Inner | 40 | 4.86 | | | |
| Plastic | Inner | 40 | 4.62 | | | |
| Plastic | Inner | 8 | 13.35 | | | |
| Cardboard | Outer | 1 | 740.00 | 698.00 | 304.00 | 212.00 |
| Carton Weight: | 0.00kg | | | | | |